

ICALI-XP - INSULATED ALUMINUM CABLE WITH XLPE/PVC

ICALI-XP-500

Description

Suitable to transmitting energy with solar farms, the aluminum cable insulated with XLPE/PVC has many applications and can be used in aerial or underground systems.

Its external insulation has high mechanical resistance, allowing the conductor to be directly installed underground. It is also resistant to UV rays what results in longer lifespan when used in aerial installations. The cable ICALi-XP is manufactured with aluminum alloy 1350, compacted, class 2. It has an insulation made with cross-linked polyethylene and covered by polyvinil chloride (PVC) type ST2 with flame retardant properties.



Datasheet

Conductor Characteristics		
Cross Section (mm²)		500
Formation		51 fios
Stranding Type		Classe 2 Compacto
Diameter of Wires (mm)		3,30
Diameter of Cable (mm)		26,50
Characteristics of the Insulating Layer		
Insulation Type / Operating Temperature		XLPE / 90°C
Insulation Thickness (mm)		2,25
Diameter With Insulation (mm)		31,00
Characteristics of the Covering Layer		
Covering Layer Type		PVC ST2
Coverage Thickness (mm)		1,90
Cable Diameter with Covered Layer (mm)		34,80
Nominal Weight (kg/km)		1751,00
Electrical Characteristics		
Maximum Resistance to 20°C in DC (ohms/km)		0,0605
Maximum Resistance at 90°C in DC - Conductor (ohms/km)		-
Maximum Resistance at 20°C in AC 60Hz (ohms/km)		-
Maximum Resistance at 90°C in AC 60Hz (ohms/km)		-
Current Capacity (3 Loaded Conductors)		

In open air	-
Buried Conduit	-
Package	
Reel Type	125/100
Nominal Length (m)	500
Net Weight per Reel (kg)	-
Gross Weight per Reel With Packing (kg)	-