

TM-L - COPPER COMPRESSION TERMINAL (ONE HOLE / LONG BARREL)

TM-150-L

Description

- Purpose:** Termination of copper conductors.
- Characteristics:** High electrical conductivity and corrosion resistance. Pad with several hole diameter options and optimum electrical contact.
- Applications:** Electrical panels, circuit breaker connections, motors, machines, busbars, electrical distribution boards, among others.
- Material:** Electrolytic copper.
- Finish:** Tin plated.



Datasheet

|                                  |                                  |       |
|----------------------------------|----------------------------------|-------|
| Conductors - Cross Section (mm²) |                                  | 150   |
| Dimensions (mm)                  |                                  |       |
| Hole Diameter (mm)               |                                  | 13,8  |
| Screw*                           | Inches                           | 1/2   |
|                                  | Metric                           | M12   |
| L                                |                                  | 30,0  |
| A                                |                                  | 79,5  |
| CB                               |                                  | 38,0  |
| AF                               |                                  | 13,0  |
| D                                |                                  | 29,5  |
| E                                |                                  | 3,6   |
| Current (A)                      |                                  | 577   |
| Application Tool                 |                                  |       |
| Mechanical Pliers                | Model                            | -     |
|                                  | Die (AT-60)                      | -     |
|                                  | Hydraulic Pliers (AY/CY/AHM/AHB) |       |
| Circunferencial Die              |                                  | IU-30 |
| Hexagonal Die                    |                                  | H-30  |

| Package         |       |
|-----------------|-------|
| Qty. / Package  | 25    |
| Unit Weight (g) | 68,50 |