

TBTA - BIMETALLIC COMPRESSION TERMINAL

TBTA-500-16

Description


Purpose: Bimetallic cable to busbar termination (aluminum or ALUMOSTEEL cable to copper busbar).

Characteristics: Compression connection. Its construction (copper pad and aluminum barrel) prevents the formation of galvanic corrosion. Pad with one hole.

Applications: Power distribution lines.

Material: Electrolytic copper pad and extruded aluminum barrel. Supplied with antioxidant compound INTELTROX.

Note: For installation in regions of aggressive enviroments, it is recommended to use thermoset insulation or self-fusing tape in the connection.



Datasheet

AAC Conductor

AWG/MCM	795
Compact (mm²)	500

Dimensions (mm)

Hole Diameter (mm)	16,5
L	36,0
A	155,0
CB	76,0
E	7,5
G	18,0

Application Tool

Mechanical Pliers (AT-60 4t)	
Die (IW)	-
Qty. of Compressions	-
Hydraulic Pliers (AY/CY/AHM/AHB)	
Die (IU)	-
Die (MH)	-
Qty. of Compressions	-
Compressor+Head kit (CY-630 3m) 23t	
Die (H)	G723H

Qty. of Compressions	2
Package	
Qty. / Package	20
Unit Weight (g)	380,00